




**Gas burner compliant with European standard EN676. Operation:**

	TBG 1200 MC	TBG 1200 ME	TBG 1200 ME V	TBG 1200 ME V O2	TBG 1200 ME V CO
	mechanical two-stage progressive	electronic two-stage progressive	modulating electronic	modulating electronic	modulating electronic
Continuous modulation operation by installing P.I.D. controller in the control panel (to be ordered separately with modulation probe).	•	•			
Modulation ratio:	1:10	1:10	1:10	1:10	1:10
Low NOx and CO emissions gas burner according to European standard EN676:	class 3	class 3	class 3	class 3	class 3
Adjusting the combustion head.	•	•	•	•	•
Maintenance facilitated by the possibility of removing the mixing unit without having to remove the burner from the boiler.	•	•	•	•	•
Fixed boiler coupling flange.	•	•	•	•	•
Easy maintenance thanks to the two-sides hinge which allows the removal of the combustion head without having to remove the burner from the boiler.	•	•	•	•	•
Combustion air intake with butterfly valve. Air flow adjustment:	mechanical cam	electric servomotor	electric servomotor	electric servomotor	electric servomotor
Fully closing air damper on shutdown to avoid loss of heat through the chimney.	•	•	•	•	•
Adjustment of fan revolutions according to working stage by means of a frequency converter in order to reduce noise and electric consumption.			•	•	•
Residual oxygen (O ₂) monitoring in the fumes in order to maintain an optimal air/fuel ratio and ensure increased performance.				•	
Residual oxygen (O ₂) and carbon monoxide (CO) and monitoring of oxidizing components (H ₂) in fumes to ensure increased performance and less atmospheric pollution.					•
CE version gas train is complete with butterfly valve, operation and safety valve with electromagnetic drive, valve tightness control, minimum and maximum pressure switch, pressure regulator and gas filter.	•	•	•	•	•
Fail proof connectors for burner/gas train connection.	•	•	•	•	•
Gas train outlet:	down	up/down	up/down	up/down	up/down
Flame detection by ionisation electrode with connector for microamperometer.	•	•	•	•	•
Control panel with display diagram for working mode with indication lights.	•				
Control panel equipped either with display showing the working process and with the keyboard for the burner adjustment.		•	•	•	•
Electric protection rating:	IP54	IP54	IP54	IP54	IP54



Model	A mm	A1 mm	A2 mm	B mm	B1 mm	B2 mm	B6 mm	C mm	D mm	E mm	F mm	I mm	L mm	M mm	N mm	Pic.
TBG 1200 MC	1470	700	770	1130	780	350	360	2290	745	485	503	685	630	M20	515	6
TBG 1200 ME	1470	700	770	1130	780	350	360	2290	745	485	503	685	630	M20	515	6
TBG 1200 ME V	1470	700	770	1130	780	350	360	2290	745	485	503	685	630	M20	515	6
TBG 1200 ME V O2	1470	700	770	1130	780	350	360	2290	745	485	503	685	630	M20	515	6
TBG 1200 ME V CO	1470	700	770	1130	780	350	360	2290	745	485	503	685	630	M20	515	6



Model	Size of packaging			Weight kg
	L	P	H	
	mm			
TBG 1200 MC	1950	1680	1300	650
TBG 1200 ME	1950	1680	1300	650
TBG 1200 ME V	1950	1680	1300	665
TBG 1200 ME V O ₂	1950	1680	1300	677
TBG 1200 ME V CO	1950	1680	1300	689

	Inverter	O ₂	CO	Emissions class	Thermal output kW	Model	Part no.	Electrical supply kW	Motor	Note
Frequency 50 Hz										
				class 3	1200 ÷ 12000	TBG 1200 MC	67270020	3N AC 50Hz 400V	22	4)
				class 3	1200 ÷ 12000	TBG 1200 ME	67260010	3N AC 50Hz 400V	22	4)
				class 3	1200 ÷ 12000	TBG 1200 ME V	67260015	3N AC 50Hz 400V	22	4) 10)
				class 3	1200 ÷ 12000	TBG 1200 ME V O₂	67260016	3N AC 50Hz 400V	22	4) 10)
				class 3	1200 ÷ 12000	TBG 1200 ME V CO	67260017	3N AC 50Hz 400V	22	4) 10)
Frequency 60 Hz										
				class 3	1200 ÷ 12000	TBG 1200 MC	67275420	3N AC 60Hz 380V	22	4)
				class 3	1200 ÷ 12000	TBG 1200 ME	67265410	3N AC 60Hz 380V	22	4)
				class 3	1200 ÷ 12000	TBG 1200 ME V	on request	3N AC 60Hz 380V	22	4) 10)
				class 3	1200 ÷ 12000	TBG 1200 ME V O₂	on request	3N AC 60Hz 380V	22	4) 10)
				class 3	1200 ÷ 12000	TBG 1200 ME V CO	on request	3N AC 60Hz 380V	22	4) 10)

TO COMPLETE THE BURNER

DESCRIPTION
TBG 1200 ME V: modulating probe for LCM 100 (see page 294)

MODULATING MODE

DESCRIPTION	PART NO.
TBG 1200 MC: modulation kit	98000055
TBG 1200 ME: modulation kit	98000059
TBG 1200 MC/1200 ME: modulating probe (see page 294)	

ACCESSORIES AVAILABLE ON REQUEST

DESCRIPTION	PART NO.
Soundproof burner cover (see page 299)	97980061

GAS BURNERS ACCESSORIES

Boiler coupling kit.

NOTES

- 4 Equipped with air closure device.
 10 Inverter supplied separately, not included on the machine.
 Net calorific value at reference conditions of 0°C, 1013mbar:
 Natural gas: Hi = 35,80 MJ/m³ = 8550 kcal/m³,
 For different type of gas and pressure values, please get in contact with our commercial department.